



No Lesen : PC003359

Licence No :

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to

VIMAX TRADING SDN. BHD.
NO 3, JALAN TPP 14
TAMAN PERINDUSTRIAN PUTRA
47130 PUCHONG
SELANGOR, MALAYSIA

Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on

CONTROLLED DOOR CLOSING DEVICE (DOOR CLOSER)

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan
as complying with

BS EN 1154 : 1997

Nur Fadhilah binti Muhammad
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.

SIRIM QAS International Sdn. Bhd.
(No. Syarikat 199601037981(410334-X))

1, Persiaran Dato' Menteri
Seksyen 2, Peti Surat 7035
40700 Shah Alam
Selangor Darul Ehsan
MALAYSIA.

Tel : 603-5544 6400
Emel : cserviceqas@sirim.my

<https://www.sirim-gas.com.my>
<https://www.malysiancertified.com.my>

Tarikh Mula Pensijilan : 22 December 2017

Certified Since

Sah Sehingga : 22 December 2024

Valid Until

Tarikh Dikeluarkan : 27 December 2023

Issue Date

No Siri : 093091

Serial No

Lesen ini dianugerahkan tertakuk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.

SCHEDULE

VIMAX TRADING SDN. BHD.



Trade Mark : VSP
Model : MODEL = DC-51
Rating : PRODUCT CLASSIFICATION = 4 8 3 0 1 3 CLASSIFICATION DETAILS ; GRADE 4 (USE FOR CLOSING DOORS FROM AT LEAST 180 DEGREE OPEN), GRADE 8 (DURABILITY OF 500,000 TEST CYCLES), GRADE 3 (POWER SIZE 3), GRADE 0 (NOT SUITABLE USE ON FIRE/SMOKE DOOR ASSEMBLIES), GRADE 1 (SAFETY GRADE 1) GRADE 3 (HIGH CORROSION RESISTANCE)

Type : OVERHEAD DOOR CLOSER SURFACE MOUNTED

Trade Mark : VSP
Model : MODEL = DC-062
Rating : PRODUCT CLASSIFICATION = 3 - 4 8 2 - 4 0 1 3 CLASSIFICATION DETAILS ; GRADE 3 (USE FOR CLOSING DOORS FROM AT LEAST 105 DEGREE OPEN), GRADE 4 (USE FOR CLOSING DOORS FROM AT LEAST 180 DEGREE OPEN), GRADE 8 (DURABILITY OF 500,000 TEST CYCLES), GRADE 2 - 4 (POWER SIZE 2 - 4), GRADE 0 (NOT SUITABLE USE ON FIRE/SMOKE DOOR ASSEMBLIES), GRADE 1 (SAFETY GRADE 1) GRADE 3 (HIGH CORROSION RESISTANCE)

Type : OVERHEAD DOOR CLOSER SURFACE MOUNTED

End of page
